



Manufacturer's Instructions and Information

Sample Description: 15G UHMWPE/polyester(recycled post-consumer)/spandex liner with nitrile coating

Product Style/Order No: JFG513-07, JFG513-08, JFG513-09, JFG513-10, JFG513-11


Product code/colour: Black

Risks against which the PPE is intended to protect:

<p>The gloves are employed and intended to protective against mechanical risks of abrasion, TDM cut, tear, puncture of palm in working environment.</p> <p>The gloves meet the requirement for resistance to puncture, may not be suitable for protection against sharply pointed objects such as hypodermic needles.</p> <p>The gloves are not to be used for chemical protection, naked flame, electrical protection or use where a risk of entanglement by moving parts.</p> <p>The composition of gloves do not contain substances which are known to cause allergies</p>		
Risk	Standard Clause	Assessment method
Abrasion	EN 388:2016+A1:2018 Clause 6.1	Abrasion resistance numbers of rubs
Cut	EN 388:2016+A1:2018 Clause 6.3	Cut resistance strength
Tear	EN 388:2016+A1:2018 Clause 6.4	Tear resistance strength
Puncture	EN 388:2016+A1:2018 Clause 6.5	Puncture resistance strength

CE This product has been labelled with a CE mark in conformity with the provisions of Module B of the Regulation (EU) 2016/425 Personal Protective Equipment

Pictograms and Performance Levels of certified gloves:

<p>EN 388: 2016+A1:2018</p>  <p>4X42C</p>	Performance	Performance levels
	Abrasion resistance	Level 4
	Blade cut level	X
	Cut resistance (EN 13997)	Level C
	Tear resistance level	Level 4
	puncture resistance	Level 2
	Impact protection	Blank
<p>X: indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material</p>		

Interpretation of the levels of performance (according to EN 388:2016+A1:2018)

Test	Level 1	Level 2	Level 3	Level 4	Level 5	
6.1 Abrasion resistance (number of rubs)	100	500	2 000	8 000	-	
6.4 Tear resistance (N)	10	25	50	75	-	
6.5 Puncture resistance (N)	20	60	100	150	-	
	Level A	Level B	Level C	Level D	Level E	Level F
6.3 TDM: cut resistance (N)	2	5	10	15	22	30

Storage: Always store in clean, dry conditions. Do NOT store in places subject to direct, strong sunlight.

Available Sizes & Selection:

Fit according to hand size Allowance built in for comfort. Check the fit before using in working conditions

Unit: mm

Glove size	Hand length	Hand circumference
7/S	171	174
8/M	178	180
9/L	185	196
10/XL	192	204
11/XXL	199	214

Limitations of Use:

Safety required only if the right size of the gloves is used and applied. Please check any damage before using. The special features may be restricted or even lost if it is excessive dirty and damaged, please replace it with a new glove.

Warning:

The gloves are not to be used for chemical protection, naked flame, electrical protection or use where a risk of entanglement by moving parts. The gloves meet the requirement for resistance to puncture, may not be suitable for protection against sharply pointed objects such as hypodermic needles. The gloves cannot be washed.

Disposal: Follow local disposal rule

Aftercare: The glove is not washable.

Manufacturer: P.F. Cusack

Address: 1 Dundee Way, Enfield, EN3 7SX, United Kingdom

EU declaration of conformity can be accessed at: www.cusack.co.uk

Detailed content of the Instructions and information notice is the responsibility for manufacture

Made in China

EU type-examination for Regulation (EU) 2016/425 by

Notified Body Number: 0598

SGS Fimko Oy, Takomotie 8, FI-00380 Helsinki, Finland.