

Q Flame Q-Flame Two Tone Coverall 4kA - 300g

Technical Data Sheet

This garment complies with the following standards:

















Size (cm)	38	41	44	48	52	55	58	62
	S	M	L	XL	2XL	3XL	4XL	5XL
Size Ref	96	104	112	120	132	138	148	158
Chest	110	118	126	134	146	152	162	172

Standards:

EN ISO 13688-2013 EN ISO 20471-2013 Class 3 EN1149-3-2004 & EN1149-5-2008 EN ISO 11611:2015 (Class 1-A1-A2) EN ISO 11612:2015 (A1-A2-B1-C1) EN61482-1-2:2007: Box Test, Class 1 4kA

EN61482-1-1:2009: Open Arc Test, ATPV: 10.8 cal/cm² IEC 61482-2:2009

Specifications:

- Material: 60% Modacrylic, 38% Cotton, 2% Anti Static
- 1 Back Pocket
- 2 Front Breast Pockets
- For use in infrastructure and allied industries (splatter protection)
- Protection against heat and flame
- Protection against Electric Arc to: Class 1 (4kA)
- Electrostatic protection
- Protection against chemicals
- Knee pad pockets

Q-Flame Two Tone Coverall - 300g

ASFBHVYN











Aftercare:

Machine Wash 40°C. Do Not Tumble Dry. One Dot Iron-Low Heat. Do Not Use Soap. Do Not Bleach. Use Detergent Only. Do Not Dry Clean.

Limitation of Use:

Limited flame spread properties will be reduced if contaminated with flammable liquids. This garment does not provide protection against electric shock.

To ensure the flame resistant and anti-static properties of this garment are fully utilised it should be worn in conjunction with suitable PPE conforming to the relevant standard.

Workers wearing the electrostatic dissipative protective clothing shall be properly earthed. Electrostatic dissipative protective clothing shall not be opened or removed whilst in the presence of flammable or explosive atmospheres without prior approval of the responsible safety engineer. The electrostatic dissipative performance of the clothing can be affected by wear and tear, laundering and possible contamination.

Electrostatic dissipative performance of the clothing shall permanently cover all none-complying materials during normal use (including bending and movements).

Repair and Modification:

DO NOT attempt repairs. DO NOT modify this garment.

Always store in clean, dry conditions, DO NOT store in places subject to direct strong sunlight. This garment must be kept clean to be effective. Replace if permanently stained or faded. Ensure when wearing the garments all zips/buttons and fasteners are closed.

P. F. Cusack Tools Supplies Ltd. Address: 1 Dundee Way Brimsdown Enfield

London EN3 7SX

Tel: +44 020 8344 4100 Fax: +44 020 8443 4794 sales@cusack.co.uk www.cusack.co.uk