



Manufacturer's Instructions and Information

Sample Description: 15G polyester (recycled post-consumer) liner with latex coating

Product Style/Order No: JFG505-07, JFG505-08, JFG505-09, JFG505-10, JFG505-11

Product code/colour: Black

Risks against which the PPE is intended to protect:

The gloves are employed and intended to protective against mechanical risks of abrasion, blade cut, TDM cut, tear, puncture of palm in working environment.

The gloves meet the requirement for resistance to puncture, may not be suitable for protection against sharply pointed objects such as hypodermic needles.

The gloves are not to be used for chemical protection, naked flame, electrical protection or use where a risk of entanglement by moving parts.

Risk	Standard Clause	Assessment method
Abrasion	EN 388:2016+A1:2018 Clause 6.1	Abrasion resistance numbers of rubs
Blade cut	EN 388:2016+A1:2018 Clause 6.2	Blade cut resistance index
Cut	EN 388:2016+A1:2018 Clause 6.3	Cut resistance strength
Tear	EN 388:2016+A1:2018 Clause 6.4	Tear resistance strength
Puncture	EN 388:2016+A1:2018 Clause 6.5	Puncture resistance strength



This product has been labelled with a CE mark in conformity with the provisions of Module B of the Regulation (EU) 2016/425 Personal Protective Equipment

Pictograms and Performance Levels of certified gloves:

EN 388: 2016+A1:2018  2121A	Performance	Performance levels
	Abrasion resistance	Level 2
	Blade cut level	Level 1
	Cut resistance (EN 13997)	Level A
	Tear resistance level	Level 2
	Puncture resistance	Level 1
	Impact protection	Blank

Interpretation of the levels of performance (according to EN 388:2016+A1:2018)

Test	Level 1	Level 2	Level 3	Level 4	Level 5	
6.1 Abrasion resistance (number of rubs)	100	500	2 000	8 000	-	
6.2 Coupe test: Blade cut resistance (index)	1,2	2,5	5,0	10,0	20,0	
6.4 Tear resistance (N)	10	25	50	75	-	
6.5 Puncture resistance (N)	20	60	100	150	-	
	Level A	Level B	Level C	Level D	Level E	Level F
6.3 TDM: cut resistance (N)	2	5	10	15	22	30

Storage: Always store in clean, dry conditions. Do NOT store in places subject to direct, strong sunlight.

Available Sizes & Selection:

Fit according to hand size Allowance built in for comfort. Check the fit before using in working conditions

Unit: mm

Glove size	Hand length	Hand circumference
7/S	171	170
8/M	181	184
9/L	188	194
10/XL	195	202
11/XXL	202	210

Limitations of Use:

Safety required only if the right size of the gloves is used and applied. Please check any damage before using. The special features may be restricted or even lost if it is excessive dirty and damaged, please replace it with a new glove.

Warning:

The gloves are not to be used for chemical protection, naked flame, electrical protection or use where a risk of entanglement by moving parts. The gloves meet the requirement for resistance to puncture, may not be suitable for protection against sharply pointed objects such as hypodermic needles. The gloves cannot be washed. The glove contains latex which may cause allergic reactions.

Disposal: Follow local disposal rule.

Aftercare: The glove is not washable.

Manufacturer: P.F. Cusack

Address: 1 Dundee Way, Enfield, EN3 7SX, United Kingdom

EU declaration of conformity can be accessed at: www.cusack.co.uk

Detailed content of the Instructions and information notice is the responsibility for manufacture

Made in China

EU type-examination for Regulation (EU) 2016/425 by

Notified Body Number: 0598

SGS Fimko Oy, Takomotie 8, FI-00380 Helsinki, Finland.