

Q Flame Q-Flame Hi Vis Long Sleeve Polo 200g

Technical Data Sheet

This garment complies with the following standards:















Mens	S	М	L	XL	2L	3XL	4XL
Chest (cm)	86-94	94-102	102-110	110-118	118-126	126-134	134-142

Standards:

EN ISO 20471 Class 3 EN ISO 13688-2013 IEC 61482-2:2009 EN61482-1-2:2007 Box Test: Class 1 4kA EN61482-1-1:2009

Open Arc Test: ATPV: 6.8 cal/cm²

EN ISO 11612:2015 A1-B1-C2

EN1149-3-2004 EN1149-5-2008

Specifications:

- Fabric: 200g, 60% Modacrylic, 38% Cotton, 2% Antistatic
- Concealed 3 button placket
- · Protection against heat and flame
- · Elasticated cuffs
- · Inherent flame retardant fabric
- Sizes S 4XL

Q-Flame Hi Vis Yellow Long Sleeve Polo - 200g

ASFBY











Aftercare:

Machine Wash 40°C. Do Not Tumble Dry. One Dot Iron-Low Heat. Do Not Use Soap. Do Not Bleach. Use Detergent Only. Do Not Dry Clean.

Limitation of Use:

Limited flame spread properties will be reduced if contaminated with flammable liquids. This garment does not provide protection against electric shock.

To ensure the flame resistant and anti-static properties of this garment are fully utilised it should be worn in conjunction with suitable PPE conforming to the relevant standard.

Workers wearing the electrostatic dissipative protective clothing shall be properly earthed. Electrostatic dissipative protective clothing shall not be opened or removed whilst in the presence of flammable or explosive atmospheres without prior approval of the responsible safety engineer. The electrostatic dissipative performance of the clothing can be affected by wear and tear, laundering and possible contamination.

Electrostatic dissipative performance of the clothing shall permanently cover all none-complying materials during normal use (including bending and movements).

Repair and Modification:

DO NOT attempt repairs. DO NOT modify this garment.

Always store in clean, dry conditions, DO NOT store in places subject to direct strong sunlight. This garment must be kept clean to be effective. Replace if permanently stained or faded. Ensure when wearing the garments all zips/buttons and fasteners are closed.

P. F. Cusack Tools Supplies Ltd. Address: 1 Dundee Way Brimsdown Enfield London EN3 7SX

Tel: +44 020 8344 4100 Fax: +44 020 8443 4794 sales@cusack.co.uk www.cusack.co.uk